



Chain Oil Spray

Highly water resistant formula

Description

Tacky, adhesive and water-insoluble chain lubricant designed for food industry equipment where there is a possibility of incidental food contact.

Properties

Chain Oil Spray meets the FDA requirements for lubricants with incidental food contact, 21 CFR 178.3570 and is NSF H1 registered.

Chain Oil doesn't contain animal derivatives and allergens listed in Annex II of directive 2011/1169/EC.

Chain Oil Spray is designed to provide high temperature and long term lubrication without deposit formation.

Chain Oil Spray is tacky and highly adhesive and limits the risks of splashing.

Chain Oil Spray is highly water and steam resistant.

Chain Oil Spray protects against rust and corrosion.

Chain Oil Spray extends chain life.

Chain Oil Spray is usable from -15°C to $+190^{\circ}\text{C}$.

Applications

Chain Oil Spray is recommended for the lubrication of machinery used in food and beverage processing and packaging industry.

Chain Oil Spray is particularly recommended for greasing of chains, cables, cams, pinions and gears that are exposed to water or steam.

Chain Oil Spray is also recommended for various mechanisms exposed to acidic juices or alkaline liquors.

Specifications

	Unit	Value
Appearance	-	Liquid
Colour	-	Practically colourless
Propellant gas	-	B/P / CO ₂
Volume	ml	400
NSF Registration	-	158905

Health/Safety

For information about safe handling and use of this product, refer to the Material Safety Data Sheet.

Storage & Handling

Caution pressurized container: protect from sunlight and other heat sources.

Use by Date

3 years after manufacture

Manufacture date can be identified from bottom of bottle as follows:

1. First 3 numbers indicate the day of the specific year (159 – means 159th day of the given year)
2. Letter to indicate production run on the day (A, B, C etc.)
3. Number to indicate filling line (between 1 and 5)
4. Last number for example 9 indicates the year – 2019

Note

The data contained in this publication is based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, this data does not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.



Terms & Conditions: © 2018. All rights reserved to Moove Lubricants Limited. Mobil and Mobil products named in this material are registered brands and trademarks of Exxon Mobil Corporation or one of its subsidiaries, licensed for use to Moove Lubricants Limited who are responsible for this document and the use of such trademarks within it. No part of this document or any trademark is permitted to be copied, reproduced or otherwise used or applied without prior consent.

Manufactured by Moove Lubricants Limited.
Operations Plant Dering Way, Gravesend, Kent DA12 2QX +44 (0) 1474 564 311